

Data sheet for three-phase Squirrel-Cage-Motors



Ordering data : 1LA9130-2KA62

without (standard)

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Electrical data:

Rated motor voltage :		(6) 400 VD/690 VY, 50 Hz, 460 VD, 60 Hz					
Frequency :		50 Hz			60 Hz		
Rated power :		5.50 kW			6.30 kW		
Rated motor speed :		2930 1/ min			3530 1/ min		
Rated motor torque :		17.9 Nm			17.0 Nm		
Rated motor current (IE) :		VD	VY		VD		
		10.10 A	5.86 A		9.80 A		
Starting / rated motor current :		7.0			7.5		
Breakdown / rated motor		3.2			3.4		
Starting / rated motor torque :		2.7			2.4		
		4/4	3/4	2/4	4/4	3/4	2/4
Efficiency %		87.0%	87.0%	86.0%	88.5%	88.5%	87.5%
Power factor :		0.90	0.88	0.83	0.91	0.89	0.85
Efficiency class :		IE2			IE2		

Mechanical data:

Sound pressure level 50Hz/60Hz (load) :	68 dB(A)	72 dB(A)
Moment of inertia :	0.019 kg*m ²	
Bearing DE :	6208 2ZC3	
Bearing NDE :	6208 2ZC3	
Type of bearing :	Floating bearings pre-loaded DE (standard)	
Condensate drainage holes :	No	
Regreasing device :	No	
Lubricants :	Esso Unirex N3	
Grease lifetime/Relubrication interval :	40000 h	
Quantity of grease for relubrication :	null g	
External earthing terminal :	No	
Coating :	Special paint finish RAL 7030 stone gray	

Environmental conditions:

Ambient temperature :	-20 °C - +40 °C
Altitude above sea level :	1000 m
Standards and specifications :	IEC, DIN, ISO, VDE, EN

General data:

Frame size	132 S
Type of construction :	(2) IM B14 / V18 / V19, standard flange
Weight in kg, without optional accessories :	43.00 kg
Frame material :	Aluminum
Degree of protection :	IP 55
Method of cooling, TEFC :	IC 411
Vibration class :	A (Standard)
Insulation :	155(F) to 130(B)
Duty type :	S1 - continuous duty
Direction of rotation :	Bi-directional

Terminal box:

Material of terminal box :	Aluminum
Type of terminal box :	gk 230
Contact screw thread :	M4
Max. cross-sectional area :	6.00 mm ²
Cable diameter from ... to ... :	11.00 mm - 21.00 mm
Cable entry :	
Cable gland :	

Special design: