

/medias/en!hp.ec.br.pr//medias/en!hp.pv/212.178.145.106NU1019-XL-M1NU10Zylinderrollenlager

# Cylindrical roller bearings

## NU1019-XL-M1 (Series NU10)

main dimensions to DIN 5412-1, non-locating bearing,  
separable, with cage

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue selection system ([https://www.schaeffler.de/content.schaeffler.de/en/news\\_media/index.jsp](https://www.schaeffler.de/content.schaeffler.de/en/news_media/index.jsp)) or by telephone on +49 (91 32) 82 - 28 97.

d	95 mm
D	145 mm
B	24 mm
D <sub>1</sub>	127,9 mm
D <sub>a</sub>	138 mm
max	
d <sub>a</sub>	106 mm
max	
d <sub>a</sub>	101 mm
min	
d <sub>b</sub>	111 mm
min	
E	132 mm
F	108 mm
r <sub>1</sub>	1,1 mm
min	
r <sub>a1</sub>	1 mm
max	
r <sub>a</sub>	1,5 mm
max	
r <sub>min</sub>	1,5 mm
s	3,1 mm Axial displacement facility from central position
m	1,42 kg Mass
C <sub>r</sub>	113000 N Basic dynamic load rating, radial

C <sub>0r</sub>	130000 N	Basic static load rating, radial
C <sub>ur</sub>	16800 N	Fatigue limit load, radial
n <sub>G</sub>	8100 1/min	Limiting speed
n <sub>B</sub>	4350 1/min	Reference speed



