


3GVA072004-BSC

ABB contact for Netherlands



"No longer for sale" replaced by [3GVA072003-BSD](#)

General Information

Product ID:	3GVA072004-BSC
ABB Type Designation:	M2VA 71C 4
Catalog Description:	No Description Available

Categories

Products » Motors and Generators » IEC Low Voltage AC Motors » Legacy IEC Low Voltage Motors » Aluminum Motors

Products » Motors and Generators » IEC Low Voltage AC Motors » Legacy IEC Low Voltage Motors » Marine General Purpose Motors

Additional Information

ABB Type Designation:	M2VA 71C 4
Altitude:	1000 m
Ambient Temperature:	40 °C
Bearing:	6203-2ZC3
Bearing NDE:	6202-2ZC3
Catalog Description:	No Description Available
Core Credit:	0.00
Country of Origin:	Italy (IT)
Customs Tariff Number:	85015100
Direction of Rotation:	Both sides

Electrical Data:

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	380-420 V	0.55 kW	1410 r/min	1.50 A	0.730	77.30 %	3.74 N·m	4.80
D	--	50 Hz	220-240 V	0.55 kW	1410 r/min	2.60 A	0.730	77.30 %	3.74 N·m	4.80
Y	--	60 Hz	440-480 V	0.65 kW	1690 r/min	1.50 A	0.770	77.30 %	3.74 N·m	4.80
D	--	60 Hz	250-280 V	0.65 kW	1690 r/min	2.60 A	0.770	77.30 %	3.74 N·m	4.80

IC Class:	IC411
IM Class:	IMB5 IM3001
Insulation Class:	ICLF
IP Class:	IP 55
Lubrication:	For life
Made To Order:	No
Minimum Order Quantity:	1.000 piece
Moment of Inertia:	0.00110 kg/m³
Output Power:	0.55 kW
Package Level 1 Units:	1 carton
Poles (High):	4
Product Name:	3-Phase squirrel cage motor
Product Net Weight:	7.000 kg
Quote Only:	No
Replaced Product ID (OLD):	3GVA072004-BSB 3GVA072004-BSCS

Replacement Product ID (NEW):	3GVA072003-BSC
Selling Unit of Measure:	3GVA072003-BSD piece
Sound dB (A):	45 dB(A)
Standard:	IEC 60034-1
Starting of Motor:	Direct Online
Temperature Class Default:	--
Terminator Box Location:	D-End top
Two Speed Motor:	No
Type of Duty:	S1
Voltage Code:	S

