



Figure similar

### MLFB-Ordering data

6SL3210-5BB22-2AV0

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Rated data	General tech. specifications																										
<b>Input</b> <table> <tr> <td>Number of phases</td><td>1 AC</td></tr> <tr> <td>Line voltage</td><td>200 ... 240 V -10 % +10 %</td></tr> <tr> <td>Line frequency</td><td>47 ... 63 Hz</td></tr> </table>	Number of phases	1 AC	Line voltage	200 ... 240 V -10 % +10 %	Line frequency	47 ... 63 Hz	<table> <tr> <td>Power factor <math>\lambda</math></td><td>0.72</td></tr> <tr> <td>Offset factor <math>\cos \varphi</math></td><td>0.95</td></tr> <tr> <td>Efficiency <math>\eta</math></td><td>0.98</td></tr> </table>	Power factor $\lambda$	0.72	Offset factor $\cos \varphi$	0.95	Efficiency $\eta$	0.98														
Number of phases	1 AC																										
Line voltage	200 ... 240 V -10 % +10 %																										
Line frequency	47 ... 63 Hz																										
Power factor $\lambda$	0.72																										
Offset factor $\cos \varphi$	0.95																										
Efficiency $\eta$	0.98																										
<b>Output</b> <table> <tr> <td>Number of phases</td><td>3 AC</td></tr> <tr> <td>Rated voltage</td><td>230 V</td></tr> <tr> <td>Rated power (HO)</td><td>2.20 kW / 3.00 hp</td></tr> <tr> <td>Rated power (LO)</td><td>2.20 kW / 3.00 hp</td></tr> <tr> <td>Rated current (HO)</td><td>11.00 A</td></tr> <tr> <td>Rated current (LO)</td><td>11.00 A</td></tr> <tr> <td>Pulse frequency</td><td>2.00 kHz</td></tr> <tr> <td>Output frequency</td><td>0 ... 550 Hz</td></tr> </table>	Number of phases	3 AC	Rated voltage	230 V	Rated power (HO)	2.20 kW / 3.00 hp	Rated power (LO)	2.20 kW / 3.00 hp	Rated current (HO)	11.00 A	Rated current (LO)	11.00 A	Pulse frequency	2.00 kHz	Output frequency	0 ... 550 Hz	<b>Ambient conditions</b> <table> <tr> <td>Cooling</td><td>External fan</td></tr> <tr> <td>Installation altitude</td><td>1000 m (3281 ft)</td></tr> </table> <b>Ambient temperature</b> <table> <tr> <td>Operation</td><td>-10 ... 60 °C (14 ... 140 °F)</td></tr> <tr> <td>Storage</td><td>-40 ... 70 °C (-40 ... 158 °F)</td></tr> </table> <b>Relative humidity</b> <table> <tr> <td>Max. operation</td><td>95 %</td></tr> </table>	Cooling	External fan	Installation altitude	1000 m (3281 ft)	Operation	-10 ... 60 °C (14 ... 140 °F)	Storage	-40 ... 70 °C (-40 ... 158 °F)	Max. operation	95 %
Number of phases	3 AC																										
Rated voltage	230 V																										
Rated power (HO)	2.20 kW / 3.00 hp																										
Rated power (LO)	2.20 kW / 3.00 hp																										
Rated current (HO)	11.00 A																										
Rated current (LO)	11.00 A																										
Pulse frequency	2.00 kHz																										
Output frequency	0 ... 550 Hz																										
Cooling	External fan																										
Installation altitude	1000 m (3281 ft)																										
Operation	-10 ... 60 °C (14 ... 140 °F)																										
Storage	-40 ... 70 °C (-40 ... 158 °F)																										
Max. operation	95 %																										
	<b>Communication</b> <table> <tr> <td>Communication</td><td>USS, Modbus RTU</td></tr> </table>	Communication	USS, Modbus RTU																								
Communication	USS, Modbus RTU																										
	<b>Standards</b> <table> <tr> <td>Compliance with standards</td><td>CE, cULus, C-Tick (RCM), KC</td></tr> <tr> <td>CE marking</td><td>EN 61800-5-1 /EN 60204-1 and EN 61800-3</td></tr> </table>	Compliance with standards	CE, cULus, C-Tick (RCM), KC	CE marking	EN 61800-5-1 /EN 60204-1 and EN 61800-3																						
Compliance with standards	CE, cULus, C-Tick (RCM), KC																										
CE marking	EN 61800-5-1 /EN 60204-1 and EN 61800-3																										

### Overload capability

#### Low Overload (LO)

110 % rated output current for 60 s, cycle time 300 s

#### High Overload (HO)

150 % rated output current for 60 s, cycle time 300 s

MLFB-Ordering data

6SL3210-5BB22-2AV0



Figure similar

### Mechanical data

Mounting position	Through-hole mounting / wall mounting / side-by-side mounting
Degree of protection	IP20
Size	FSC
Net weight	2.50 kg ( 5.51 lb )
Width	184.0 mm ( 7.24 in )
Height	182.0 mm ( 7.17 in )
Depth	169.0 mm ( 6.65 in )

### Connections

#### Max. motor cable length

Shielded	25 m (82 ft)
Unshielded	50 m (164 ft)

### Inputs / outputs

#### Standard digital inputs

Number	4
--------	---

#### Digital outputs

Number as relay changeover contact	1
------------------------------------	---

Number as transistor	1
----------------------	---

#### Analog inputs

Number	2 (Can be used as additional digital input)
--------	---

#### Analog outputs

Number	1
--------	---