

/medias/en!hp.ec.br.pr//medias/en!hp.pv/212.178.145.106NU215-E-XLNU2..-EZylinderrollenlager

Cylindrical roller bearings

NU215-E-XL-TVP2 (Series NU2..-E)

main dimensions to DIN 5412-1, non-locating bearing,
separable, with cage

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue selection system (https://www.schaeffler.de/content.schaeffler.de/en/news_media/index.jsp) or by telephone on +49 (91 32) 82 - 28 97.

d	75 mm
D	130 mm
B	25 mm
D ₁	114,4 mm
D _a max	121 mm
d _a max	87 mm
d _a min	84 mm
d _b min	90 mm
E	118,5 mm
F	88,5 mm
r ₁ min	1,5 mm
r _{a1} max	1,5 mm
r _a max	1,5 mm
r _{min}	1,5 mm
s	1,2 mm Axial displacement facility from central position
m	1,27 kg Mass
C _r	155000 N Basic dynamic load rating, radial

C_{0r}	157000 N	Basic static load rating, radial
C_{ur}	21700 N	Fatigue limit load, radial
n_G	6500 1/min	Limiting speed
n_B	4400 1/min	Reference speed



