

Data sheet for three-phase Squirrel-Cage-Motors



Ordering data : 1LA9090-6KA10

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Electrical data:

Rated motor voltage :	(1) 230 VD/400 VY, 50 Hz, 460 VY, 60 Hz					
Frequency :	50 Hz		60 Hz			
Rated power :	0.75 kW		0.86 kW			
Rated motor speed :	925 1/ min		1125 1/ min			
Rated motor torque :	7.7 Nm		7.3 Nm			
Rated motor current (IE) :	VD	VY		VY		
	3.44 A	1.98 A		2.05 A		
Starting / rated motor current :	4.4		4.9			
Breakdown / rated motor	2.5		2.6			
Starting / rated motor torque :	3.0		2.6			
	4/4	3/4	2/4	4/4	3/4	2/4
Efficiency %	75.9%	75.9%	72.9%	80.0%	80.0%	79.0%
Power factor :	0.72	0.63	0.52	0.66	0.57	0.40
Efficiency class :	IE2		IE2			

Mechanical data:

Sound pressure level 50 Hz/60Hz (load) :	43 dB(A)	47 dB(A)
Moment of inertia :	0.0033 kg*m ²	
Bearing DE :	6205 2ZC3	
Bearing NDE :	6004 2ZC3	
Type of bearing :	Floating bearings pre-loaded DE (standard)	
Condensate drainage holes :	No	
Regreasing device :	No	
Lubricants :	Esso Unirex N3	
Grease lifetime/Relubrication interval :	40000 h	
Quantity of grease for relubrication :	null g	
External earthing terminal :	No	
Coating :	Special paint finish RAL 7030 stone gray	

Explosion protection:

Type of protection : without (standard)

Environmental conditions:

Ambient temperature : -20 °C - +40 °C
Altitude above sea level : 1000 m
Standards and specifications : IEC, DIN, ISO, VDE, EN

General data:

Frame size	090 S
Type of construction :	(0) IM B3 / B6 / B7 / B8 / V5 without canopy
Weight in kg, without optional accessories :	15.70 kg
Frame material :	Aluminum
Degree of protection :	IP 55
Method of cooling, TEFC :	IC 411
Vibration class :	A (Standard)
Insulation :	155(F) to 130(B)
Duty type :	S1 - continuous duty
Direction of rotation :	Bi-directional

Terminal box:

Material of terminal box :	Aluminum
Type of terminal box :	gk 030
Contact screw thread :	M4
Max. cross-sectional area :	1.50 mm ²
Cable diameter from ... to ... :	9.00 mm - 17.00 mm
Cable entry :	1xM25x1,5-1xM16x1,5
Cable gland :	2 plugs

Special design: