

/medias/en!hp.ec.br.pr//medias/en!hp.pv/212.178.145.106NUP2236NUP22..-EZylinderrollenlager

Cylindrical roller bearings

NUP2236-E-XL-M1 (Series NUP22..-E)

main dimensions to DIN 5412-1, locating bearing,
separable, with cage

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue selection system (https://www.schaeffler.de/content.schaeffler.de/en/news_media/index.jsp) or by telephone on +49 (91 32) 82 - 28 97.

d	180 mm
D	320 mm
B	86 mm
B ₃	12 mm
D ₁	280 mm
d ₁	229 mm
D _a max	303 mm
d _a min	197 mm
d _c min	233 mm
E	291 mm
F	215 mm
r ₁ min	4 mm
r _a max	3 mm
r _{min}	4 mm
m	31,6 kg Mass
C _r	1180000 N Basic dynamic load rating, radial
C _{0r}	1490000 N Basic static load rating, radial

Cur	223000 N	Fatigue limit load, radial
nc	3200 1/min	Limiting speed
nb	1380 1/min	Reference speed



