



MLFB-Ordering data: 1LE1003-1DB23-4AB4-Z
R11

Motor type: 1AV3162B

Client order no.:

Item no.:

Order no.:

Consignment no.:

Offer no.:

Project:

Remarks:

U	Δ/Y	f	P	P	I	n	M	NOM. EFF at ... load [%]			Power factor at ... load			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _A /I _N	T _f /T _N	T _B /T _N	
400	Δ	50	11.00	- / -	20.50	1475	71.0	91.4	91.9	91.4	0.84	0.80	0.70	6.8	2.2	3.2	IE3
690	Y	50	11.00	- / -	12.00	1475	71.0	91.4	91.9	91.4	0.84	0.80	0.70	6.8	2.2	3.2	IE3
460	Δ	60	12.60	- / -	20.00	1775	68.0	92.4	92.7	92.1	0.85	0.81	0.73	7.1	2.0	3.2	IE3
460	Δ	60	11.00	- / -	18.00	1780	59.0	92.4	92.4	91.3	0.83	0.78	0.68	7.9	2.3	3.7	IE3
IM B3 / IM 1001			FS 160 M		83 kg	IP55	CC032A	IEC/EN 60034		IEC, DIN, ISO, VDE, EN							

Mechanical data		
Sound pressure level 50Hz/60Hz (load)	65 dB(A)	69 dB(A)
Moment of inertia	0.071 kg m²	
Bearing DE NDE	6209 2Z C3	6209 2Z C3
Bearing lifetime	40000 h	
Lubricants	Esso Unirex N3	
Regreasing device	No	
Grease nipple	- / -	
Type of bearing	Locating bearing NDE	
Condensate drainage holes	No	
External earthing terminal		
Vibration class	A	
Insulation	155(F) to 130(B)	
Duty type	S1	
Direction of rotation	bidirectional	
Frame material	aluminum	
Data of anti condensation heating	-/-	
Coating (paint finish)	Standard paint finish C2	
Color, paint shade	RAL7030	
Motor protection	(B) 3 PTC thermistors - for tripping (2 terminals)	
Method of cooling	IC411 - self ventilated, surface cooled	

Terminal box	
Terminal box position	top
Material of terminal box	Aluminium
Type of terminal box	TB1 J00
Contact screw thread	M5
Max. cross-sectional area	16.0 mm²
Cable diameter from ... to ...	19.0 mm - 28.0 mm
Cable entry	2xM40x1,5-1xM16x1,5
Cable gland	3 plugs

Special design (1)

R11 Terminal box rotated through 90°, cable entry from NDE

Environmental conditions	
Ambient temperature	-20 °C - +40 °C
Altitude above sea level	1000 m